



# Exterior Camera Mount IV-7100K



- Medium indoor / outdoor enclosures
- Spring assisted forward opening lid
- Optional field installed heaters, blower and sun shield
- Temperature reduced by 4°F (2°C) with sun shield
- 2 cable entry cord grips on bottom of enclosure with minimum diameter of .24" (6mm) and maximum diameter of .41" (10mm)
- Aluminum construction

### KEY FEATURES

MODEL TYPE	IV-7100K
Input Voltage	24 VAC
Power	Heater: 25W Blower: 2.3W
Construction	Aluminum
Viewing Window	2.13" (53mm)
Max. Size Camera & Lens	6.85" x 3.45" x 2.85" (174x90x72.5mm)
Heater & Blower Activates	ON: 32°F ± 9°F (0°C ± 5°C) OFF: 68°F (20°C)
Blower Activates	ON: 95°F ± 9°F (35°C ± 5°C) OFF: 72°F (20°C)
Weight – Camera housing	3.60 lbs. (1.64 kg)
Weight – Mounting brkt.	1.92 lbs. (.87 kg)
Gross Weight (STI-7100)	4.72 lbs. (2.14 kg)
Gross Weight (STI-7100K)	6.9 lbs. (3.1 kg)

Image Vault Customer Service / Technical Support

1-888-462-4382

[www.Image-Vault.com](http://www.Image-Vault.com)