

A SAFE EQUAL TO THE TASK.



JC 4524

COMPOSITE TL-15 CHESTS WITH OMEGA POINT 350° 1-HOUR FIRE LABEL

When you are protecting assets reaching into the tens and hundreds of thousands of dollars, you'll want a safe equal to the task. These safes pass a grueling physical entry attack test that includes heavy power tools, sledgehammers and picks. Each safe features high-quality dial combination locks with an internal relocking device. The Composite TL-15 Chest is available in either our Graphite or Taupe finishes.



KC 6524

COMPOSITE TL-30 CHESTS WITH OMEGA POINT 350° 1-HOUR FIRE LABEL

- Standard 3-way boltwork.
- Equipped with saddle in secondary lock position for field installation of secondary lock.
- Available in either our Graphite or Taupe finishes.

The TL-30 rating means the safe is designed and tested to withstand double attack time as the very respectable TL-15.



KX 7233

COMPOSITE TL-30x6 CHESTS WITH OMEGA POINT 350° 1-HOUR FIRE LABEL

- Standard 3-way boltwork.
- Equipped with saddle in secondary lock position for field installation of secondary lock.

The TL-30x6 means that you take the 30-minute attack specifications for a standard TL-30, and apply those requirements to all 6 sides of the container. Combined with other enhancements, this is the most superior safe available for protecting your most valuable documents, cash, or other assets.



OMEGA POINT FIRE RATINGS

The products that carry an Omega Point Laboratories listing tend to be developed for the home user, rather than an office or industrial environment. **1-HOUR RATING:** Composite Chests come with an Omega Point 350° F 1-Hour fire label. The safe is tested for 1 hour in a furnace with temperatures rising to 1700° F. The internal temperature of the safe must not rise more than 275° F for the duration of the test.

SAFE SPECIFICATIONS

	Model	Interior Size			Exterior Size			Interior Shelves	Door Opening		Capacity	Weight
		H	W	D	H	W	D ¹		H	W		
JC SERIES	JC 1814-1	18"	14"	12¼"	25"	21"	21¼"	1	18"	14"	3,087 cu in.	700 lbs.
	JC 2218-1	22"	18 ⁵ / ₈ "	16"	28½"	25 ¹ / ₈ "	26 ⁷ / ₈ "	1	22"	18 ⁵ / ₈ "	6,556 cu in.	1,000 lbs.
	JC 3020-1	30"	20"	21"	36½"	26½"	31 ⁷ / ₈ "	2	30"	20"	12,600 cu in.	1,400 lbs.
	JC 3624-1	36"	24"	21"	42½"	30 ⁵ / ₈ "	31 ⁷ / ₈ "	2	36"	24"	18,144 cu in.	1,830 lbs.
	JC 4524-1	45"	24"	21"	51½"	30 ⁵ / ₈ "	31 ⁷ / ₈ "	3	45"	24"	22,680 cu in.	2,115 lbs.
	JC 5524-1	55"	24"	21"	61½"	30 ⁵ / ₈ "	31 ⁷ / ₈ "	4	55"	24"	27,720 cu in.	2,250 lbs.
	JC 6033-1	60"	33 ⁷ / ₈ "	21"	66½"	41"	31 ⁷ / ₈ "	4	60"	33 ⁷ / ₈ "	42,683 cu in.	3,200 lbs.
	JC 6524-1	65"	24"	21"	71½"	31"	31 ⁷ / ₈ "	5	65"	24"	32,760 cu in.	2,760 lbs.
	JC 6528-1	65"	28"	21"	71½"	35 ¹ / ₈ "	31 ⁷ / ₈ "	5	65"	28"	38,220 cu in.	3,130 lbs.
	JC 7233-1	72"	33 ⁷ / ₈ "	21"	78½"	41"	31 ⁷ / ₈ "	5	72"	33 ⁷ / ₈ "	51,219 cu in.	3,650 lbs.
JC 7233XD-1	72"	33 ⁷ / ₈ "	26"	78½"	41"	36 ⁷ / ₈ "	5	72"	33 ⁷ / ₈ "	63,414 cu in.	4,125 lbs.	
KC SERIES	KC 1814-1	18"	14"	12¼"	25"	21"	21¼"	1	18"	14"	3,087 cu in.	700 lbs.
	KC 2218-1	22"	18 ⁵ / ₈ "	16"	28½"	25 ¹ / ₈ "	26 ⁷ / ₈ "	1	22"	18 ⁵ / ₈ "	6,556 cu in.	1,050 lbs.
	KC 3020-1	30"	20"	21"	36½"	26½"	31 ⁷ / ₈ "	2	30"	20"	12,600 cu in.	1,450 lbs.
	KC 3624-1	36"	24"	21"	42½"	30 ⁵ / ₈ "	31 ⁷ / ₈ "	2	36"	24"	18,144 cu in.	1,850 lbs.
	KC 4524-1	45"	24"	21"	51½"	30 ⁵ / ₈ "	31 ⁷ / ₈ "	3	45"	24"	22,680 cu in.	2,135 lbs.
	KC 5524-1	55"	24"	21"	61½"	30 ⁵ / ₈ "	31 ⁷ / ₈ "	4	55"	24"	27,720 cu in.	2,550 lbs.
	KC 6033-1	60"	33 ⁷ / ₈ "	21"	66½"	41"	31 ⁷ / ₈ "	4	60"	33 ⁷ / ₈ "	42,683 cu in.	3,300 lbs.
	KC 6524-1	65"	24"	21"	71½"	31"	31 ⁷ / ₈ "	5	65"	24"	32,760 cu in.	2,900 lbs.
	KC 6528-1	65"	28"	21"	71½"	35 ¹ / ₈ "	31 ⁷ / ₈ "	5	65"	28"	38,220 cu in.	3,200 lbs.
	KC 7233-1	72"	33 ⁷ / ₈ "	21"	78½"	41"	31 ⁷ / ₈ "	5	72"	33 ⁷ / ₈ "	51,219 cu in.	3,725 lbs.
KC 7233XD-1	72"	33 ⁷ / ₈ "	26"	78½"	41"	36 ⁷ / ₈ "	5	72"	33 ⁷ / ₈ "	63,414 cu in.	4,200 lbs.	
KX SERIES	KX 3624-1	36"	24"	21"	42½"	30 ⁵ / ₈ "	31 ⁷ / ₈ "	2	36"	24"	18,144 cu in.	2,100 lbs.
	KX 4524-1	45"	24"	21"	51½"	30 ⁵ / ₈ "	31 ⁷ / ₈ "	3	45"	24"	22,680 cu in.	2,300 lbs.
	KX 5524-1	55"	24"	21"	61½"	30 ⁵ / ₈ "	31 ⁷ / ₈ "	4	55"	24"	27,720 cu in.	2,750 lbs.
	KX 6033-1	60"	33 ⁷ / ₈ "	21"	66½"	41"	31 ⁷ / ₈ "	4	60"	33 ⁷ / ₈ "	42,683 cu in.	3,550 lbs.
	KX 6524-1	65"	24"	21"	71½"	31"	31 ⁷ / ₈ "	5	65"	24"	32,760 cu in.	3,150 lbs.
	KX 6528-1	65"	28"	21"	71½"	35 ¹ / ₈ "	31 ⁷ / ₈ "	5	65"	28"	38,220 cu in.	3,425 lbs.
	KX 7233-1	72"	33 ⁷ / ₈ "	21"	78½"	41"	31 ⁷ / ₈ "	5	72"	33 ⁷ / ₈ "	51,219 cu in.	4,025 lbs.
	KX 7233XD-1	72"	33 ⁷ / ₈ "	26"	78½"	41"	36 ⁷ / ₈ "	5	72"	33 ⁷ / ₈ "	63,414 cu in.	4,550 lbs.

¹Outside depth includes handle and dial.



The best records protection you can buy.

101 Security Parkway, New Albany, IN 47150 – 1.800.457.2424 – www.firekingoffice.com

A member of the **FireKing** Security Group.