



The Turtle. Evolved.

Introducing **Turtle Contour**

Radiused Edges

4-Pin Key Lock

Design-Forward

Accommodates Letter and Legal File Sizes

Recessed Handles

Superior Scratch Resistance



Country of Origin

Made in USA

Fire Warranty

Free After-Fire Replacement

Compliance

UL 1 HR 1700° F



Same Trusted Turtle Protection Refined for the Modern Workspace

Built on FireKing's proven Turtle platform, the new FireKing® Turtle Contour modernizes an icon—combining certified fire protection with a refined design made for today's front-office environments. Made in the USA, Turtle Contour is UL Listed for fire endurance, impact, and explosion-hazard protection, ETL Verified for digital media protection, and is water-resistant. And because it's FireKing, it's backed by our Free After-Fire Replacement Guarantee: if your Turtle Contour is ever damaged in a fire, we'll replace it free of charge. Visit fireking.com for details.



1 HR 1700°F



IMPACT RATED



½ HR RATING



WATER RESISTANT

Designed for Spaces Where Style Matters as Much as Performance


TURTLE CONTOUR

AVAILABLE IN:



BL

Black



AW

Arctic White



PL

Platinum



PA

Parchment

DESIGNER COLORS AVAILABLE FOR SPECIAL ORDER:




MA

Calcutta Marble




KP

Knotty Pine



LC

Light Chestnut



LW

Light Walnut



MODEL	2 DRAWER 2C1822-CPA 2C1822-CAW 2C1822-CBL 2C1822-CPL			4 DRAWER 4C1822-CPA 4C1822-CAW 4C1822-CBL 4C1822-CPL		
DIMENSIONS						
EXTERIOR	17 ³ / ₄ " W	22 ¹ / ₈ " D	27 ³ / ₄ " H	17 ³ / ₄ " W	22 ¹ / ₈ " D	52 ³ / ₄ " H
EXTERIOR WITH DRAWER OPEN	17 ³ / ₄ " W	41 ¹ / ₈ " D	27 ³ / ₄ " H	17 ³ / ₄ " W	41 ¹ / ₈ " D	52 ³ / ₄ " H
INTERIOR DRAWER	12 ³ / ₁₆ " W	15 ¹ / ₈ " D	10 ³ / ₈ " H	12 ³ / ₁₆ " W	15 ¹ / ₈ " D	10 ³ / ₈ " H
LOCK	4-Pin Key Lock					
DRAWER BODIES	High Side for Hanging Folders; Maintenance-Free Telescoping Suspension					
NET WEIGHT	221 lbs (Shipping Weight 251 lbs)			405 lbs (Shipping Weight 435 lbs)		
INSULATION MATERIAL	Proprietary Gypsum Blend Reinforced by 14-Gauge Galvanized Welded Steel Wire					
FINISH	Powder-Coated for Superior Scratch, Scuff, and Stain Resistance					
FIRE RATED	Yes. 1700°F (927°C) for 1 hour [UL 72 Class 350]					
DIGITAL MEDIA PROTECTION RATED	ETL ½ HR 1550°F					
EXPLOSION HAZARD TESTED	Yes. The product is placed in a pre-heated 2000°F furnace to verify that it withstands rapid heating without structural failure.					
FIRE + IMPACT TESTED	Yes. The product is heated, dropped 30 feet to simulate a building collapse, followed by an additional 30-minute fire endurance test.					
WATER RESISTANT	Yes. IP65—Designed to prevent water damage resulting from sprinklers and fire hoses in the event of a fire.					
WARRANTY	Limited Lifetime Warranty to the original owner, with a free replacement after-fire guarantee.					

